PRODUCT INFORMATION SHEET

BROKIS



Name GEOMETRIC OVAL 1/3 TOP

Type pendent lamp

ID PC1147

Description

Geometric accentuates the aesthetic expression and structure of BROKISGLASS, which itself is remarkably distinctive. The collection is defined by basic geometric shapes that characterize the overall contours of the lights and instil them with a singular graphic element to achieve a striking contrast with the animate, almost sculptural makeup of the glass. The suspension components make up the glass geometric shapes, their edges rendered in black profiles. The circular and oval lights work well as solitary pieces, and multiples can also be arranged in a sort of jigsaw puzzle, which in the hands of architects results in an endless variety of lighting combinations. The concept surpasses its primary function as a lighting fixture and opens the door to large-format blocks of light and other uncommon compositions. For even more expressive freedom and a truly bespoke lighting experience, clients can specify a different colour of glass in each of the two sections of a light. Resting against a sturdy cylindrical base, the Geometric Table elicits a subtle aesthetic tension that amplifies the overall visual experience. The Geometric collection has received a technological upgrade in the form of precision-milled dural for the metal profiles. In keeping with the brand's ongoing development of new technologies at the highest levels of quality and innovation, this year the Geometric collection has received a technological upgrade, whereby the metal profile has been reworked in precision-milled dural with new glass inserts made of improved BROKISGLASS. The dural profile accentuates the lines of the light as a whole and its details, which now feature fewer connecting elements. The BROKISGLASS has been enhanced with an opal back layer that increases the diffusion of the light. The collection also offers several dimming options for greater comfort and flexibility in setting the right mood, and the Tunable White function lets the user adjust the colour temperature of the light.

Technical description

The technologies applied in the Geometric collection are based on the principles of recycling, sustainability, and eco-friendly production. The base material used in making the lights is the waste glass generated in the production of other Brokis collections. The recycled glass material is subjected to several stages of processing, combining traditional glassmaking techniques (hand grinding, sandblasting) with modern ones (melt moulding, waterjet cutting, mould shaping) and resulting in a unique product that embodies both tradition and modernity. Each piece is an unrepeatable original with its own story. Flawless scattering of light is provided by an LED panel with optical lenses. The glass components can be easily changed for other colour variations. The TIG welded metal frame is crafted by hand with the same degree of precision as the rest of the light.

Glass Colour

triplex opal BROKISGLASS	A	CGC2676
smoke grey BROKISGLASS	A	CGC2677
smoke brown BROKISGLASS	A	CGC2720
yellow - triplex opal BROKISGLASS	A	CGC2722
light pink - triplex opal BROKISGLASS	A	CGC2723
orange - triplex opal BROKISGLASS	A	CGC2724
red - triplex opal BROKISGLASS	A	CGC2725
light blue - triplex opal BROKISGLASS	A	CGC2726
turquoise - triplex opal BROKISGLASS	A	CGC2727
dark green - triplex opal BROKISGLASS	A	CGC2804
green apple - triplex opal BROKISGLASS	A	CGC2728
amber - triplex opal BROKISGLASS	A	CGC2730
cognac - triplex opal BROKISGLASS	A	CGC2731
grey - triplex opal BROKISGLASS	A	CGC2747

Glass surface

glossy finish (front face)	A	CGSU2736
acid-etched finish (front face)	A	CGSU2737

Body finish

metal - black matte powder coating with structure	A	CCS2673

Canopy

metal - black matte powder coating with structure	A	CCSC2674

Cable colour

textile cable - black	A	CECL519

LED Source

DIM, 24V, LED, 10W, 2700K, 1416lm, RA90+	A	LEDS2781
DIM (TW), 24V, LED, 10W, 1800K-6500K, 866-1390lm, RA90+	A	LEDS2967

Dimmable version

non-dimmable version	A	CEDV1457
DIM RF system - remote control version	A	CEDV1461
DIM PWM signal	A	CEDV1459
DIM 1-10V	A	CEDV1460
DIM DALI version	A	CEDV1458
DIM CASAMBI CBU-PWM4	A	CEDV2854
DIM (TW) CASAMBI CBU-PWM4	A	CEDV2942
DIM (TW) DALI version	A	CEDV2944