PRODUCT INFORMATION SHEET

BROKIS

Name	MONA MEDIUM FLOOR
Type	floor lamp
ID	PC980



Description

The Mona collection is based on the concept of penetrating forms. The light source boldly traverses the ample volume of smooth handblown glass to reveal the thrilling tension inherent in the design. The collection's essence, however, lies in its unconventional construction and refined combination of materials. It also boasts dimmable tubular LED light sources, developed by BROKIS, each with a different colour temperature. The entire Mona family has been technologically improved with innovative connectors and the replacement of the wood components with metal ones. These improvements make it easier to change out the light source and clean the lights. The wall variant is dimmable via an integrated dimmer in the lower part of the metal fixture. The family comprises several sizes (S, M, L, XL) and various types of lights (pendant, floor, table, wall).

Technical description

Combined craftsmanship / hand-blown glass in combination with metal body. The craftsmanship applied in production follows in the centuries-old tradition and experience of master glassmakers. The precision crafting of hand-blown glass instills distinctive, enduring character and outstanding quality in all BROKIS products. The glass shades are formed from multiple layers of molten glass, each of which is scrutinized by the master glassmaker prior to being blown into the mold. Up to 70% of the resulting quality is achieved in this stage of production.

Glass Colour

transparent glass	A	CGC23
smoke grey - transparent glass	A	CGC516
smoke brown - transparent glass	A	CGC538
opaline - transparent glass	A	CGC38
black - transparent glass	A	CGC602
violet - transparent glass	A	CGC554

Glass surface

glossy surface	A	CGSU66

Body finish

metal - black matte powder coating	A	CCS846
metal - white matte powder coating	A	CCS845

Connection method

BROKIS connector 24V	A	CCM1019

Cable colour

textile cable - black	A	CECL519
textile cable - white	A	CECL521

LED Source

24V, LED, 7.7W, 2700K, 327lm, RA90+, DIM	A	LEDS1989
24V, LED, 7.7W, 4000K, 360lm, RA90+, DIM	A	LEDS1990
24V, LED, 7.7W, 5000K, 387lm, RA90+, DIM	A	LEDS1991

Dimmable version

non-dimmable version	A	CEDV1457
DIM RF system - remote control version	A	CEDV1461
DIM CASAMBI CBU-PWM4	A	CEDV2854