# PRODUCT INFORMATION SHEET

BROKIS



**Name** PLANETS MINI 4

**Type** pendent lamp

**ID** PC1362

**Description**

The Planets family of lights is expanding with a new collection called Planets MINI, bringing the same elegance and versatility as the original collection but in a more compact form. The reduced size allows for larger compositions even in standard interiors with lower ceilings or less floor space. Planets MINI retain the unique system of counterweights and pulleys, enabling effortless height adjustment and flexible arrangements, from single pendants to compositions featuring up to twelve lights. The counterweights are precisely calibrated to the mass of each light, ensuring smooth and secure adjustments. The fixtures are equipped with a round LED panel beneath a matte glass diffuser, which conceals the internal components while preserving the silhouette of the light. Matte metal elements and monochrome textile cables emphasize the collection's clean lines and cohesive aesthetic. Available in the elementary geometric shapes of sphere, cone, and capsule, Planets MINI come in three elegant glass finishes: smoky grey matte, triplex opal matte, and smoke brown matte. This variety offers endless possibilities for creative compositions and adaptable lighting solutions for diverse spaces. With their smaller scale, Planets MINI can be effortlessly installed where the original version might not be suitable, creating a refined and inviting atmosphere in any intimate interior.

**Technical description**

The techniques Brokis applies in the production of glass are rooted in centuries of tradition and require remarkable skill from master glassmakers. Precision crafting of handblown glass gives each product a distinctive character and unmatched quality. The glass shades are formed from multiple layers of molten glass, each of which is thoroughly scrutinized by the glassmaker before being blown into the mould. The triplex opal glass of the shades represents one of the finest materials used in the lighting industry today. Together with carefully guarded handcraft techniques, the sandwich structure of two transparent outer layers of crystal and an inner layer of white opal between them lends the glass outstanding visual properties. The metal component is manufactured through a unique stamping technique that has been proven over the course of millennia and involves spinning cold sheet metal on a rotating form. The history of this technology dates to Celtic times. As with the glassmakers, the master metalworkers draw upon tradition and experience that have been passed down through the ages and give the final product exceptional added value. The metal fixtures, ceiling canopies, and power cables are available in either white or anthracite grey.

## Glass Colour

| | | |
|---|---|---|
| smoke grey - transparent glass | A | CGC516 |
| smoke brown - transparent glass | A | CGC538 |
| triplex opal | A | CGC39 |

## Glass surface

| | | |
|---|---|---|
| acid-etched both side surface | A | CGSU881 |

## Body finish

| | | |
|---|---|---|
| metal - black matte powder coating with structure | A | CCS2673 |
| metal - white matte powder coating with structure | A | CCS2809 |
| metal - pearl gold powder coating | A | CCS3061 |

## Canopy

| | | |
|---|---|---|
| metal - black matte powder coating with structure | A | CCSC2674 |
| metal - white matte powder coating with structure | A | CCSC2810 |
| metal - pearl gold powder coating | A | CCSC3062 |

## Cable colour

| | | |
|---|---|---|
| textile cable - black | A | CECL519 |
| textile cable - white | A | CECL521 |
| textile cable - light brown | A | CECL3063 |

## LED Source

| | | |
|---|---|---|
| DIM, 24V, LED, 6.5W, 2700K, 735lm, RA90+ | A | LEDS2953 |
| DIM (TW), 24V, LED, 6.5W, 1800K-6500K, 498lm-805lm, RA90 | A | LEDS2992 |

## Dimmable version

| | | |
|---|---|---|
| non-dimmable version | A | CEDV1457 |
| DIM RF system - remote control version | A | CEDV1461 |
| DIM 1-10V | A | CEDV1460 |
| DIM DALI version | A | CEDV1458 |
| DIM AC phase-cut, ELV | A | CEDV1730 |
| DIM CASAMBI CBU-PWM4 | A | CEDV2854 |
| DIM (TW) CASAMBI CBU-PWM4 | A | CEDV2942 |
| DIM (TW) DALI version | A | CEDV2944 |