PRODUCT INFORMATION SHEET

BROKIS



Name	PURO ECLECTIC RECTANGULAR SET 1000
Type	pendent lamp
ID	PC1115
Description	Puro Eclectic is a suspension light composition comprising handblown Puro tubes. Puro is a boldly minimalistic variation on atmospheric pendant lights. Inspiration for the collection and its name come from the Spanish word for “cigar”, which also means “pure” and is a reference to the composition’s clean lines. The diffused glow of the tubes to elicit a dynamic ambience, while the alternating gloss and matte finishes provide a degree of provocation. The primary aim was to create a simple yet linearly dynamic and expressive composition to hang above dining tables. The name Eclectic was chosen based on the variously adjustable diagonal and intercommunicating glass tubes.
Technical description	The craftsmanship applied in production follows in the centuries-old tradition and experience of master glassmakers. The precision crafting of hand-blown glass instills distinctive, enduring character and outstanding quality in all Brokis products. The glass shades are formed from multiple layers of molten glass, each of which is scrutinized by the master glassmaker prior to being blown into the mold. Up to 70% of the resulting quality is achieved in this stage of production

Glass Colour

triplex opal	A	CGC39
dark grey - opaline	B	CGC1507

Glass surface

acid-etched both side surface	A	CGSU881

Body finish

metal - black matte powder coating	A	CCS846
metal - white matte powder coating	A	CCS845

Canopy

metal - black matte powder coating	A	CCSC619
metal - white matte powder coating	A	CCSC618

Connection method

BROKIS connector 24V	A	CCM1019

Cable colour

textile cable - black	A	CECL519
textile cable - white	A	CECL521

LED Source

1000mm 24V, LED, 25W, 2700K, 1910lm, RA90+, DIM	A	LEDS1932
1000mm 24V, LED, 25W, 4000K, 2115lm, RA90+, DIM	A	LEDS1933
1000mm 24V, LED, 25W, 5000K, 2260lm, RA90+, DIM	A	LEDS1934

Dimmable version

non-dimmable version	A	CEDV1457
DIM RF system - remote control version	A	CEDV1461
DIM PWM signal	A	CEDV1459
DIM 1-10V	A	CEDV1460
DIM DALI version	A	CEDV1458
DIM AC phase-cut, ELV	A	CEDV1730
DIM CASAMBI CBU-PWM4	A	CEDV2854