# PRODUCT INFORMATION SHEET

BROKIS



| | |
|---|---|
| **Name** | PURO SINGLE HORIZONTAL 400 |
| **Type** | pendent lamp |
| **ID** | PC1158 |
| **Description** | Puro is a boldly minimalistic variation on atmospheric pendant lights. Inspiration for the collection and its name come from the Spanish word for “cigar”, which also means “pure” and is a reference to the composition’s clean lines. The Puro collection comprises of single vertical or horizontal tube or a single bell light suspended beneath a vertical tube and dual bell lights suspended beneath a horizontal tube. The diffused glow of the tubes combines with that of the bells to elicit a dynamic ambience, while the alternating gloss and matte finishes provide a degree of provocation. When standing alone as single tubes, amazing installations can be created, such as a composition of tubes coupled to a screen dividing space and evoking an intimate atmosphere bordering on scenography. Puro offers atmospheric room lighting as well as lighting for offices, hospitality interiors, boutiques, showrooms and private dining areas. |
| **Technical description** | The craftsmanship applied in production follows in the centuries-old tradition and experience of master glassmakers. The precision crafting of hand-blown glass instills distinctive, enduring character and outstanding quality in all Brokis products. The glass shades are formed from multiple layers of molten glass, each of which is scrutinized by the master glassmaker prior to being blown into the mold. Up to 70% of the resulting quality is achieved in this stage of production. |

## Glass Colour

| | | |
|---|---|---|
| triplex opal | A | CGC39 |
| dark grey - opaline | B | CGC1507 |

## Glass surface

| | | |
|---|---|---|
| acid-etched both side surface | A | CGSU881 |

## Body finish

| | | |
|---|---|---|
| metal - black matte powder coating | A | CCS846 |
| metal - white matte powder coating | A | CCS845 |

## Canopy

| | | |
|---|---|---|
| glass - black | A | CCSC2404 |
| glass - white | A | CCSC2403 |
| Trimless – cable version – white structure, h 11-18 mm | A | CCSC2903 |
| Trimless – cable version – black structure, h 11-18 mm | A | CCSC2904 |
| Trimless – cable version – white structure, h 25-33 mm | A | CCSC3064 |
| Trimless – cable version – black structure, h 25-33 mm | A | CCSC3065 |
| Keeport – cable version – white structure | A | CCSC3158 |
| Keeport – cable version – black structure | A | CCSC3159 |

## Connection method

| | | |
|---|---|---|
| BROKIS connector 24V | A | CCM1019 |

## Cable colour

| | | |
|---|---|---|
| textile cable - black | A | CECL519 |
| textile cable - white | A | CECL521 |

## LED Source

| | | |
|---|---|---|
| 400mm 24V, LED, 11W, 2700K, 595lm, RA90+, DIM | A | LEDS2744 |
| 400mm 24V, LED, 11W, 4000K, 659lm, RA90+, DIM | A | LEDS2745 |
| 400mm 24V, LED, 11W, 5000K, 705lm, RA90+, DIM | A | LEDS2746 |

## Dimmable version

| | | |
|---|---|---|
| non-dimmable version | A | CEDV1457 |
| DIM RF system - remote control version | A | CEDV1461 |
| DIM PWM signal | A | CEDV1459 |
| DIM 1-10V | A | CEDV1460 |
| DIM DALI version | A | CEDV1458 |
| DIM AC phase-cut, ELV | A | CEDV1730 |
| DIM CASAMBI CBU-PWM4 | A | CEDV2854 |