PRODUCT INFORMATION SHEET

BROKIS

Name UNDER PRESSURE VERTICAL MORE

Type pendent lamp

ID PC1389



Description

The fleeting moment when molten glass becomes a solid yet infinitely delicate object – such is the inspiration for Under Pressure, a bold new collection of lights that captures this transformation and the exciting tension it creates. That singular, magical instance when hot molten glass succumbs to pressure and begins to assume its final form, an embodiment of strength and fragility in one. The dynamic glass shapes appear still alive, evoking an image of organic deformation from external forces, an invisible pressure bending them to its will. This striking visual effect is further accentuated with technical elements, such as a centre-line threaded rod that penetrates the delicate glass globe and brings a touch of geometric regularity and industrial elegance. Under Pressure delivers an impressive contrast, an alluring juxtaposition of the organic malleability of glass and uncompromising precision of metal. The lights are manufactured in assorted sizes and typologies, backed with a broad spectrum of glass colour and surface finish options, for a look that always catches the eye and elevates the aesthetics of any interior. Under Pressure is now also available as a table light.

Technical description

Glass Colour

transparent glass	A	CGC23
smoke grey - transparent glass	A	CGC516
smoke brown - transparent glass	A	CGC538
opaline - transparent glass	A	CGC38
amber - transparent glass	A	CGC515
pearl grey - opaline glass	A	CGC1916
pearl brown - opaline glass	A	CGC3050
pearl amber - opaline glass	A	CGC3058

Glass surface

glossy surface	A	CGSU66

Ornaments

without ornaments	A	CGO2988
crackle	A	CGO3051

Body finish

brushed black lacquer	A	CCS3052
brushed champagne lacquer	A	CCS3000
brushed bronze lacquer	A	CCS3002

Canopy

Keeport – cable version – white structure	A	CCSC3158
brushed black lacquer	A	CCSC3057
brushed champagne lacquer	A	CCSC3001
brushed bronze lacquer	A	CCSC3003
Keeport – cable version – black structure	A	CCSC3159

Connection method

BROKIS connector 24V	A	CCM1019

Cable colour

textile cable - black	A	CECL519
textile cable - light grey	A	CECL1918

LED Source of the bottom part

24V, LED, 2.5W, 2700K, 250lm, RA90, DIM	A	CEBBP3168

LED Source

24V, LED, 2.5W, 2700K, 250lm, RA90, DIM	A	LEDS3078

Dimmable version

non-dimmable version	A	CEDV1457
DIM RF system - remote control version	A	CEDV1461
DIM 1-10V	A	CEDV1460
DIM DALI version	A	CEDV1458
DIM AC phase-cut, ELV	A	CEDV1730
TRIAC - STANDARD OPTION	A	CEDV2865
DIM CASAMBI CBU-PWM4	A	CEDV2854